January 17, 2018



East Building, PHH – 30 1200 New Jersey Avenue, Southeast Washington, D.C. 20590

Pipeline and Hazardous Materials Safety Administration

DOT-SP 10232 (TWENTYFIRST REVISION)

EXPIRATION DATE: 2021-11-30

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. <u>GRANTEE</u>: ITW Sexton Decatur, AL

2. PURPOSE AND LIMITATIONS:

a. This special permit authorizes the manufacture, marking, sale, and use of a non-DOT specification packaging conforming in part with the DOT Specification 2Q, except as specified herein, for the transportation in commerce of the material authorized in this special permit. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.

b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.

c. In accordance with 49 CFR 107.107(a) party status may not be granted to a manufacturing permit. These packaging may be used in accordance with 49 CFR 173.22a

- 3. <u>REGULATORY SYSTEM AFFECTED</u>: 49 CFR Parts 106, 107 and 171-180.
- 4. <u>REGULATIONS FROM WHICH EXEMPTED</u>: 49 CFR § 173.304(d) in that DOT specification containers are required and §§ 173.306(i) and 173.167 in that only aerosols may be transported as a limited quantity, except as specified herein.

Page 2 January 17, 2018

5. <u>BASIS</u>: This special permit is based on the application of ITW Sexton dated December 15, 2017, submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identi- fication Number	Packing Group
Compressed gas, flammable, n.o.s.(2,3,3,3 Tetrafluoropropene or Refrigerant gas HFO-1234yf)	2.1	UN1954	N/A
Consumer commodity*	ORM-D	N/A	N/A
Consumer commodity*	9	ID8000	N/A
Liquefied gas, flammable, n.o.s.	2.1	UN3161	N/A
Liquefied gas, n.o.s. (1,3.3.3- Tetrafluoroprop-1-ene or Refrigerant gas HFO-1234ze)	2.2	UN3163	N/A
Refrigerant gases, n.o.s.	2.2	UN1078	N/A
1,1,1,2-Tetrafluoroethane	2.2	UN3159	N/A

*This proper shipping name is only authorized for Division 2.2 materials.

7. SAFETY CONTROL MEASURES:

a. <u>PACKAGING</u> - Prescribed packaging is a non-refillable non-DOT specification inside metal container conforming with Sexton Can Company drawing No. 995D0017, Revision G, dated November 26, 2007, on file with the Approvals and Permits Division. The cylinder must be in conformance with DOT Specification 2Q (§ 178.33a), except as follows: § 178.33a-6 Manufacture.

(a) * * *

(b) * * *

(1) * * *

(2) Side seams. Not permitted.

(c) Ends: The ends shall be designed to withstand pressure and bottom end is fitted with a pressure relief device (PRD).

§ 178.33a-8 Tests.

Burst Test - For qualification burst tests, each 5000 containers or less, successively produced as a batch or part thereof shall constitute a lot. Two containers, one with a PRD and one without a PRD, taken randomly from each lot and complete with the ends assembled must be pressure tested to destruction. The burst pressure of containers fitted with a bottom PRD may not be below 380 psig. The burst pressure of containers without a bottom PRD may not be less than 480 psig. If either of the test containers fails to meet the above requirements, the lot shall be rejected. However, an additional 5 randomly selected pairs of containers from that lot may be burst tested to qualify that lot. If any of the additional test containers fail the burst test, that lot must be rejected.

§ 178.33a-9 Marking.

Applies except that the container must be marked with "DOT-SP 10232" in lieu of "DOT 2Q".

b. <u>OPERATIONAL CONTROLS</u> - Each packaging must be prepared and shipped in accordance with the following:

(1) The filling density may not exceed 87 percent.

(2) Prior to initial shipment of the filled containers, each completed container must be heated until the pressure in the container is equivalent to the equilibrium pressure of the lading at 130°F. Lading

Page 4 January 17, 2018

equilibrium pressure may not exceed 240 psig at 130°F. Liquid content of lading may not completely fill the container at 130°F. Acceptable containers must show no evidence of leakage, distortion or other defect.

(3) The container must be packed in a strong outside packaging as prescribed in § 173.301(a)(9).

(4) Each outside packaging must be marked "INSIDE CONTAINERS COMPLY WITH DOT-SP 10232".

(5) Except for Division 2.1 materials, containers filled with a material meeting the definition of a "consumer commodity" in § 171.8 may be reclassed as an ORM-D and shipped as "consumer commodity" in accordance with § 173.306(i). These outside packagings are not required to be marked "INSIDE CONTAINERS COMPLY WITH DOT-SP 10232" as specified above in paragraph 7.b.(4).

(6) Except for Division 2.1 materials, containers filled with a material meeting the definition of a "consumer commodity" in § 171.8 may be reclassed and shipped as "Consumer commodity, 9, ID8000" in accordance with § 173.167. These outside packagings are not required to be marked "INSIDE CONTAINERS COMPLY WITH DOT-SP 10232" as specified above in paragraph 7.b. (4).

(7) Except for Division 2.1 materials, containers filled with a material meeting the definition of a "limited quantity" in § 171.8 may be shipped as "limited quantity" in accordance with § 173.306(i). These outside packagings are not required to be marked "INSIDE CONTAINERS COMPLY WITH DOT-SP 10232" as specified above in paragraph 7.b.(4).

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.

b. A person who is not a holder of this special permit, but receives a packaging covered by this special permit, may reoffer it for transportation provided no modification or change is made to the packaging and it is offered for

Page 5

January 17, 2018

transportation in conformance with this special permit and the HMR.

c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this special permit must be marked with a <u>registration symbol</u> designated by the Office of Hazardous Materials Special Permits and Approvals for a specific manufacturing facility.

e. A current copy of this special permit must be maintained at each facility where the package is manufactured under this special permit. It must be made available to a DOT representative upon request.

f. Test data obtained under the qualification burst test (§ 178.33a-8) of this special permit, must be kept on file and be made available upon request by Approvals and Permits Division.

- 9. <u>MODES OF TRANSPORTATION AUTHORIZED</u>: Motor vehicle, rail freight, cargo vessel, cargo aircraft only, and passengercarrying aircraft.
- 10. <u>MODAL REQUIREMENTS</u>: A current copy of this special permit must be carried aboard each cargo vessel, aircraft or motor vehicle used to transport packages covered by this special permit. The shipper shall furnish a current copy of this special permit to the air carrier before or at the time the shipment is tendered.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
 - All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
 - Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when
 applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when the special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)—"The Hazardous Materials Safety and Security Reauthorization Act of 2005" (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. <u>REPORTING REQUIREMENTS</u>: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 Immediate notice of certain hazardous materials incidents, and 171.16 Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:

Jac By

for William Schoonover Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp app/special permits/spec perm index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: CWFreeman:SG