SAFETY DATA SHEET



G3 Flux Remover UFI

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

| 1.1 Product identifier | |
|-------------------------------|--|
| Product name | : G3 Flux Remover UFI |
| Product code | : EUR1631A-16S, EUR1631-18S |
| Product description | : Fluxing agents Remover. |
| Product type | : Aerosol. |
| Other means of identification | : Fluxing agents Remover. Industrial/Professional use UFI: KP2C-W0SM-M00S-R9RX |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer Techspray 8125 Cobb Center Drive Kennesaw, GA 30152 Tel: 678-819-1408 Toll free: 1-800-858-4043 Fax: 1 806-372-8750

Distributor

Importer ITW Contamination Control Skejby Nordlandsvej 307 DK-8200 Aarhus N Denmark Tel +45 87 400 220 Fax +45 87 400 222 Email: info@itw-cc.com Website: www.Techsprayeu.com

e-mail address of person responsible for this SDS

: Importer/Only Representative Bay 150 Shannon Industrial Estate Shannon County Clare Ireland V14 DF82 +353 61 771 500 customerservice.shannon@itwpp.com

National contact

ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Tel: +31 88 1307 400 FAX: +31 88 1307 499 Website: www.Techsprayeu.com

1.4 Emergency telephone number

National advisory body/Poison Centre

| Telephone number | EMERGENCY HEALTH INFORMATION: Austria +43 1 31304 5620, Belgium +32022649636, Bulgaria +359 2 9154 409, Croatia +38514686910, Cyprus +3572240561, Czech Republic +420267082257, Denmark +45 72 54 40 00, Estonia +3726943384, Finland +358 5052 000, France +33 3 85 21 92, Germany +49-30-18412-0, Greece +302106479250, Hungary +34 (1) 476 1136, Ireland +35318092566, Italy +390649906140, Latvia +371 67032600, Lithuania +370 70662008, Luxembourg +352 24785551, Netherland +31 88 75 585 61, Norway +47 21 07 70 00, Poland +48 42 2530 400, Portugal +351213303271, Romania +40213183606, Slovakia +421 2 5465 2307, Slovenia +38614006039, Spain +34 917689800, Sweden +46104566750 United Kingdom (England or Wales) 0845 46 47 or Scotland 08454 24 24 24 (UK only). |
|-------------------------|--|
| <u>Supplier</u> | |
| Telephone number | : (800)-858-4043 |
| Hours of operation | : 8:00 AM to 5:00 PM |
| Information limitations | : EMERGENCY HEALTH INFORMATION: EMERGENCY SPILL INFORMATION: Transport information |

SECTION 2: Hazards identification

| 2.1 Classification of the sub | ostance or mixture |
|---|---|
| Product definition | : Mixture |
| Classification according to | D Regulation (EC) No. 1272/2008 [CLP/GHS] |
| Aerosol 3, H229 Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412 | |
| The product is classified as | hazardous according to Regulation (EC) 1272/2008 as amended. |
| Ingredients of unknown toxicity | 53.5 percent of the mixture consists of component(s) of unknown acute oral toxicity 56.5 percent of the mixture consists of component(s) of unknown acute dermal toxicity 53.5 percent of the mixture consists of component(s) of unknown acute inhalation toxicity |
| Ingredients of unknown ecotoxicity | : Contains 53.5% of components with unknown hazards to the aquatic environment |
| See Section 16 for the full te | ext of the H statements declared above. |
| See Section 11 for more det | ailed information on health effects and symptoms. |
| 2.2 Label elements | |
| Hazard pictograms | |
| Signal word | : Warning |

SECTION 2: Hazards identification

| Hazard statements | : | Pressurised container: may burst if heated. Harmful if swallowed or if inhaled. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. |
|---|----|--|
| Precautionary statements | | |
| Prevention | : | Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing dust or mist. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not pierce or burn, even after use. |
| Response | : | IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. |
| Storage | 1 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | 1 | trans-dichloroethylene |
| Supplemental label elements | : | Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable. |
| Special packaging requirem | en | <u>ts</u> |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do | : | None known. |

not result in classification

SECTION 3: Composition/information on ingredients

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|-------------------------|---|-----------|---|---|------|
| trans-dichloroethylene | EC: 205-860-2 CAS: 156-60-5 Index: 602-026-00-3 | ≥25 - ≤50 | Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412 | ATE [Oral] = 1235 mg/kg ATE [Inhalation (vapours)] = 11 mg/ I | [1] |
| Carbon dioxide, gas | REACH #: Annex IV | ≤5 | Press. Gas (Comp.), | - | [2] |

G3 Flux Remover UFI

SECTION 3: Composition/information on ingredients

| OLOHION S. | oomposition/intornia | | Ingreatents | | |
|------------|--|----|--|---|-----|
| | EC: 204-696-9 CAS: 124-38-9 | | H280 | | |
| ethanol | EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5 | ≤5 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above. | - | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

| Eye contact | : | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|----------------------------|---|---|
| Inhalation | : | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : | Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

SECTION 4: First aid measures

| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
|--------------|---|
| Inhalation | Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : Adverse symptoms may include the following: Ingestion Seek medical attention. |

4.3 Indication of any immediate medical attention and special treatment needed

| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
|---------------------|--|
| Specific treatments | : No specific treatment. |

SECTION 5: Firefighting measures

| 5.1 Extinguishing media Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
|--|---|
| Unsuitable extinguishing media | : None known. |

5.2 Special hazards arising from the substance or mixture

| Hazards from the substance or mixture | : | Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
|---|---|--|
| Hazardous combustion products | : | Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides |
| 5.3 Advice for firefighters | | |
| Special protective actions for fire-fighters | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | ote | ctive equipment and emergency procedures |
|---------------------------------|-----|---|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| 6.3 Methods and material for | со | ntainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. |
| 6.4 Reference to other sections | : | See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. |
|--|--|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

| Date of issue/Date of revision : 1/13/2023 Date of previous issue : 1/13/2023 Version : 26 | 6/15 |
|--|------|
|--|------|

G3 Flux Remover UFI

SECTION 7: Handling and storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

| 7.3 Spe | cific en | d use(s) |
|---------|----------|----------|
|---------|----------|----------|

Recommendations : Not available.

Industrial sector specific

solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| | EU OEL (Europe, 10/2019). Notes: list of indicative occupational exposure limit values TWA: 9000 mg/m ³ 8 hours. TWA: 5000 ppm 8 hours. |

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|-------------------------|------|--------------------------|-----------------------|-----------------------|----------|
| ethanol | DNEL | Long term Oral | 87 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 114 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 206 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 343 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 950 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 950 mg/m³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 1900 mg/ m³ | Workers | Local |

PNECs

No PNECs available

8.2 Exposure controls

SECTION 8: Exposure controls/personal protection

| Appropriate engineering controls | : | Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. |
|-------------------------------------|------|---|
| Individual protection measured | ures | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin protection | | |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : | Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |
| Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| <u>Appearance</u> | |
|--|------------------------------------|
| Physical state | : Liquid. |
| Colour | : Clear. Colourless. |
| Odour | : Characteristic. |
| Odour threshold | : Not available. |
| Melting point/freezing point | : Not available. |
| Initial boiling point and boiling range | : Not available. |
| Flammability | : Not available. |
| Lower and upper explosion limit | : Not available. |
| Flash point | : Not applicable. |
| Date of issue/Date of revision | : 1/13/2023 Date of previous issue |

G3 Flux Remover UFI

| Auto-ignition temperature | 3 | Not available. |
|-----------------------------------|----|-----------------|
| Decomposition temperature | : | Not available. |
| рН | ; | Not available. |
| Viscosity | \$ | Not available. |
| Solubility in water | ; | Not available. |
| Partition coefficient: n-octanol/ | : | Not applicable. |

water

| | V | apour Pres | sure at 20°C | V | Vapour pressure at 50°C | | | |
|---|------------|---------------|--------------|-------|-------------------------|--------|--|--|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method | | |
| Carbon dioxide, gas | 42903.49 | 5720 | | | | | | |
| ethanol | 42.95 | 5.7 | | | | | | |
| Relative density | : 1.1 | 8 | | | • | | | |
| Vapour density | : No | t available. | | | | | | |
| Particle characteristics | | | | | | | | |
| Median particle size | : No | t applicable. | | | | | | |
| .2 Other information | | | | | | | | |
| 9.2.1 Information with regar | d to physi | cal hazard | classes | | | | | |
| Explosive properties | | applicable | | | | | | |
| Oxidising properties | | t available. | | | | | | |
| Aerosol product | | | | | | | | |
| Type of aerosol | : Spi | ay | | | | | | |
| Ignition distance | : 0 c | | | | | | | |
| Enclosed space ignition - Time equivalent | : 379 |) s/m³ | | | | | | |
| Enclosed space ignition - Deflagration density | : 209 | 90 g/m³ | | | | | | |
| 9.2.2 Other safety characte | eristics | | | | | | | |
| - | | t available. | | | | | | |
| Miscible with water | | | | | | | | |

| 10.1 Reactivity | : | No specific test data related to reactivity available for this product or its ingredients. |
|--|---|--|
| 10.2 Chemical stability | : | The product is stable. |
| 10.3 Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : | Avoid all possible sources of ignition (spark or flame). |
| 10.5 Incompatible materials | : | No specific data. |
| 10.6 Hazardous decomposition products | : | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

G3 Flux Remover UFI

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|------------------------|---------|--------------------------|----------|
| trans-dichloroethylene | LC50 Inhalation Gas. | Rat | 24100 ppm | 4 hours |
| _ | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | 1235 mg/kg | - |
| ethanol | LC50 Inhalation Vapour | Rat | 124700 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 7 g/kg | - |

Conclusion/Summary : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------|------------------|-------------------|--------------------------------|-----------------------------------|--|
| trans-dichloroethylene | 1235 | N/A | 24100 | 11 | N/A |
| ethanol | 7000 | N/A | N/A | 124.7 | N/A |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------|-------------|
| trans-dichloroethylene | Eyes - Moderate irritant | Rabbit | - | 10 mg | - |
| - | Skin - Moderate irritant | Rabbit | - | 24 hours 500 | - |
| | | | | mg | |
| ethanol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | | | | mg | |
| | Eyes - Moderate irritant | Rabbit | - | 0.066666667 | - |
| | | | | minutes 100 | |
| | | | | mg | |
| | Eyes - Moderate irritant | Rabbit | - | 100 uL | - |
| | Eyes - Severe irritant | Rabbit | - | 500 mg | - |
| | Skin - Mild irritant | Rabbit | - | 400 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 | - |
| | | | | mg | |

| Conclusion/Summary | : | Not available. |
|--------------------------------|------------|-------------------------|
| Sensitisation | | |
| Conclusion/Summary | 1 | Not available. |
| <u>Mutagenicity</u> | | |
| Conclusion/Summary | : | Not available. |
| Carcinogenicity | | |
| Conclusion/Summary | 1 | Not available. |
| Reproductive toxicity | | |
| Conclusion/Summary | \$ | Not available. |
| Teratogenicity | | |
| Conclusion/Summary | \$ | Not available. |
| Specific target organ toxicity | (| <u>single exposure)</u> |
| Not available. | | |
| Specific target organ toxicity | <u>/ (</u> | repeated exposure) |

Not available.

Aspiration hazard

Not available.

| SECTION 11: Toxicol | gical information |
|--|-------------------|
| Information on likely routes of exposure | Not available. |

Potential acute health effects

| Eye contact | : Causes serious eye irritation. |
|--------------|----------------------------------|
| Inhalation | : Harmful if inhaled. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : Harmful if swallowed. |

Symptoms related to the physical, chemical and toxicological characteristics

| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
|--------------|--|
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : Adverse symptoms may include the following: Ingestion Seek medical attention. |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Short term exposure | | |
|--------------------------------|---|--|
| Potential immediate effects | : Not available. | |
| Potential delayed effects | : Not available. | |
| Long term exposure | | |
| Potential immediate effects | : Not available. | |
| Potential delayed effects | : Not available. | |
| Potential chronic health eff | <u>ects</u> | |
| Not available. | | |
| Conclusion/Summary | : Not available. | |
| General | : No known significant effects or critical hazards. | |
| Carcinogenicity | : No known significant effects or critical hazards. | |
| Mutagenicity | : No known significant effects or critical hazards. | |
| Reproductive toxicity | : No known significant effects or critical hazards. | |

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNot available.

SECTION 12: Ecological information

12.1 Toxicity

| Acute LC50 220000 µg/l Fresh water | Daphnia - Daphnia magna | 401 |
|--------------------------------------|---|---|
| | Tophina - Daprina magna | 48 hours |
| Acute EC50 17.921 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| Acute EC50 2000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| Acute LC50 25500 µg/l Marine water | Crustaceans - Artemia franciscana - Larvae | 48 hours |
| Acute LC50 42000 µg/l Fresh water | Fish - Oncorhynchus mykiss | 4 days |
| Chronic NOEC 4.995 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| Chronic NOEC 100 ul/L Fresh water | Daphnia - Daphnia magna - Neonate | 21 days |
| Chronic NOEC 0.375 ul/L Fresh water | Fish - Gambusia holbrooki - Larvae | 12 weeks |
| | Acute LC50 25500 µg/l Marine water Acute LC50 42000 µg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 100 ul/L Fresh water | Acute LC50 25500 μg/l Marine waterCrustaceans - Artemia franciscana - LarvaeAcute LC50 42000 μg/l Fresh water Chronic NOEC 4.995 mg/l Marine waterFish - Oncorhynchus mykiss Algae - Ulva pertusaChronic NOEC 100 ul/L Fresh water Chronic NOEC 0.375 ul/L Fresh waterDaphnia - Daphnia magna - NeonateChronic NOEC 0.375 ul/L Fresh waterFish - Gambusia holbrooki - Larvae |

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|-----------------------|--------|-------------------|
| trans-dichloroethylene Carbon dioxide, gas ethanol | 2.09 0.83 -0.35 | - - | low low low |

| 12.4 Mobility in soil | |
|---|------------------|
| Soil/water partition coefficient (Koc) | : Not available. |
| | |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: Not available.

12.6 Endocrine disrupting properties

Not available.

Mobility

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

| Product Methods of disposal | Disposal of with the req any regiona products via untreated to | tion of waste should be this product, solutions a juirements of environme a local authority requiren a a licensed waste dispo the sewer unless fully o | nd any by-products s ntal protection and w nents. Dispose of su sal contractor. Was | should at all time vaste disposal le urplus and non-r te should not be | es com gislatic ecyclat dispos | on and ble sed of |
|--------------------------------|--|---|--|---|---|-------------------------|
| | with jurisdic | | | | | |
| Hazardous waste | : The classifi | cation of the product ma | ay meet the criteria fo | or a hazardous w | /aste. | |
| Date of issue/Date of revision | : 1/13/2023 | Date of previous issue | : 1/13/2023 | Version | :26 | 12/15 |

G3 Flux Remover UFI

SECTION 13: Disposal considerations

Packaging

| | | _ | | |
|------|-----|------|------|-------|
| Math | ode | of | dicu | posal |
| weur | uus | 01 0 | uisi | JUSAI |

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

```
Special precautions
```

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

SECTION 14: Transport information

| | • | | | |
|------------------------------------|----------|----------|----------|-----------------------------|
| | ADR/RID | ADN | IMDG | IATA |
| 14.1 UN number or ID number | UN1950 | UN1950 | UN1950 | UN1950 |
| 14.2 UN proper shipping name | AEROSOLS | AEROSOLS | AEROSOLS | Aerosols, non- flammable |
| 14.3 Transport hazard class(es) | 2 | 2 | 2.2 | 2.2 |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | Yes. | No. | No. |

Additional information

| ADR/RI |) |
|--------|---|
| ADN | |

: <u>Tunnel code</u> (E)

The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in: Not available.bulk according to IMOinstruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation Annex XIV None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations

SECTION 15: Regulatory information

| • | | • |
|---|------------|-----------------------|
| Industrial emissions (integrated pollution prevention and control) - Air | : | Listed |
| Industrial emissions (integrated pollution prevention and control) - Water | : | Not listed |
| Ozone depleting substand Not listed. | es | <u>(1005/2009/EU)</u> |
| Prior Informed Consent (P | <u>IC)</u> | <u>(649/2012/EU)</u> |

Not listed.

Aerosol dispensers

3

63% by mass of the contents are flammable.

Seveso Directive

This product is not controlled under the Seveso Directive.

2

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

| Inventory list | | |
|--------------------------------|---|---|
| Australia | : | All components are listed or exempted. |
| Canada | : | All components are listed or exempted. |
| China | : | Not determined. |
| Eurasian Economic Union | : | Russian Federation inventory: Not determined. |
| Japan | : | Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined. |
| New Zealand | : | Not determined. |
| Philippines | : | Not determined. |
| Republic of Korea | : | All components are listed or exempted. |
| Taiwan | : | All components are listed or exempted. |
| Thailand | : | Not determined. |
| Turkey | : | Not determined. |
| United States | : | All components are active or exempted. |
| Viet Nam | : | All components are listed or exempted. |

SECTION 15: Regulatory information

| 15.2 Chemical safety | 1 | This product contains substances for which Chemical Safety Assessments are still |
|----------------------|---|--|
| assessment | | required. |

SECTION 16: Other information

| Indicates information that has changed from previously issued v | ersion. |
|---|---------|
|---|---------|

| Abbreviations and acronyms | ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group |
|----------------------------|--|
| | VPvB = Very Persistent and Very Bioaccumulative |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|-----------------------|
| Aerosol 3, H229 | On basis of test data |
| Acute Tox. 4, H302 | Calculation method |
| Acute Tox. 4, H332 | Calculation method |
| Skin Irrit. 2, H315 | Calculation method |
| Eye Irrit. 2, H319 | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Full text of abbreviated H statements

| Highly flammable liquid and vapour. |
|---|
| Pressurised container: may burst if heated. |
| Contains gas under pressure; may explode if heated. |
| Harmful if swallowed. |
| Causes skin irritation. |
| Causes serious eye irritation. |
| Harmful if inhaled. |
| Toxic to aquatic life with long lasting effects. |
| Harmful to aquatic life with long lasting effects. |
| |

Full text of classifications [CLP/GHS]

| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
|--|---|
| Aerosol 3 | AEROSOLS - Category 3 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Press. Gas (Comp.) | GASES UNDER PRESSURE - Compressed gas |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 : 1/13/2023 |
| Date of printing Date of issue/ Date of revision | : 1/13/2023 |
| Date of previous issue | e : 1/13/2023 |
| Version | : 26 |

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.